



SUPER PLATINA

UPENDE/VERWE/PAINTS

TOUGH INTERIOR



TMW



TMCW

GENERAL INFORMATION:

- An acrylic water-based paint.
- Sheen finish
- Excellent interior durability
- Excellent washability
- Excellent overcoating properties
- Low dirt pickup

RECOMMENDED USES:

- High quality washable PVA
- Direct application to newly plaster, concrete or brickworks
- Suitable for direct application to metal and wood surfaces providing the surfaces have been primed with the correct type of primer

TECHNICAL INFO:

Type:	Pure Acrylic Emulsion
Drying time:	
• Surface Dry:	1/2-2 hours (depending on temperature)
• Totally cured:	3-5 hours (depending on temperature)
Recoating time:	4 Hours
Viscosity :	100 – 115 Krebs units
Density	1.24 – 1.26
Solid content:	28% to 30%
Gloss Level:	Sheen Finish

SURFACE PREPARATION:

New work and previously painted surfaces to be prepared in line of National Home Builders Regulations (NHBC) and SABS Standards:

- Concrete cement: Prime rough surfaces first
- Wall Boards: Apply directly
- Asbestos Cement :thin down first coat up to 20% with water for deeper penetration
- PVC: Use a suitable primer
- Chalky surfaces must be primed with bonding liquid thinned down 20%
- Any loose flailing material or paint must first be removed and then primed with a suitable primer or undercoat
- Final Coat: Recommended for two coats
- Apply one coat for general Maintenance painting

APPLICATION:

- Before paint is applied it must be mixed/stirred properly
- Ready for use with brush, roller or airless spray
- Thinning recommended for porous surfaces (10 – 15%) for first coat
- The ideal application conditions are a surface ambient temperature of 10°C and a maximum of 35°C with a relative humidity of 80% maximum

PRECAUTIONS:

- Store away from direct sunlight, heat and severe cold
- Do not paint during wet or cold weather (below 10°C)
- Use containers with the same batch numbers for large areas
- Ensure the surface is well prepared and dry before applying the paint.



MATERIAL SAFETY DATA SHEET:

IDENTIFICATION

- Water Base Paint - Toxic and cannot be used for fishponds

TECHNICAL INFORMATION

- Perstorp NX795
- Acticide

HEALTH AND SAFETY

- Contact with product may cause irritation to sensitive skin
- Wear suitable gloves for hand protection
- Wear protective clothing
- Wear suitable respirator
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice

FIRST AID

- EYES – Do not rub and flush with plenty of clean water
- SKIN – Wash thoroughly with soap and water immediately after handling

FIRE FIGHTING MEASURES

- Product is not flammable

ACCIDENTAL SPILLAGE

- Washable with Clean Water (immediately)
- Hard Dry in 75 - 120 hours (depending on temperature)

PERSONAL PROTECTION

- Use eye protection
- Use rubber gloves
- Use suitable respirator
- Use protective clothing

HANDLING AND STORAGE

- Handling – Wear appropriate personal protective equipment and clothing
- Storage – Store in dry cool conditions and ensure container is sealed
- Store in a well-ventilated area away from foodstuffs and oxidising agents

TRANSPORTATION INFORMATION

- Product must be kept dry during transportation
- Low Hazard

REGULATORY INFORMATION AND PICTOGRAMS

- Classification: Irritant
- Risk Phrases: None

Safety Phrases: Wear protective clothing, respirators, gloves and eye/face protection.
In case of contact with eyes, rinse immediately with clean water.
If necessary, seek medical advice.
After contact with skin, wash immediately with clean water.
Do not take internally.
Keep out of reach of children

CONTACT INFORMATION:

✉ admin@superplatina.co.za

☎ 016 004 0131

🌐 www.superplatina.co.za

📍 Office Address: 74/75 Kroonarend Rd, Witkopdorp (Daleside), Meyerton, 1873

SUPER PLATINA PAINTS

Super Platina Paints (Pty) Ltd was established 20 years ago and shares a common platform with Hi-Tech Refractories, a leader in the supply of products and materials used in the refractory industry. As a bespoke paint company, we have succeeded in manufacturing a range of paints that are unique in many ways. We've combined the best of European technology with South African practicality at an affordable price.

COMPANY REG. NO: 2001,021579/07