



SUPER PLATINA

UPENDE/VERWE/PAINTS

TOUGH POLISH PAINT



TPPW



TPPGY



TPPR



TPPS

Super Platina Tough Polish Paint is a premium, water-based acrylic paint designed for versatile use on floors, concrete, and various surfaces. This durable paint delivers a sleek, high-gloss finish with excellent flexibility and overcoating properties. With its fast drying time and superior coverage, Tough Polish Paint is perfect for both indoor and outdoor applications, providing a tough, long-lasting protective layer.

RECOMMENDED USES

- Direct application to concrete floors.

TECHNICAL INFO

Type:	Acrylic Emulsion
Drying Time:	Depending on Wet Film Thickness (WFT), temperature & humidity.
• Touch dry:	20 minutes
Gloss Level:	Gloss finish
Flexibility:	100%
Viscosity:	90- 100 Krebs Unit
Density at 23°C:	+1.01-1.04 Std SG (depending on colour)
Solids by Volume:	5%
Spread Rate:	7-8 m ² /litre average (depending on surface, profile, application method and coating thickness).
Coats:	Recommends at least 2 coats.

SURFACE PREPARATION

- New work and previously painted surfaces to be prepared in line of National Home Builders Regulations (NHBRC), ASTM, ISO and SABS Standards
- Ensure that surfaces are sound and free from dust, oil, grease, dirt and debris. Surfaces must be thoroughly dry-no more than 15% moisture content.
- Remove loose and flaking paint with scraper.
- To kill lichen and algae growth, scrub with solution of 4:1 water/chlorine or 4:1 water/sodium hypochlorite. Rinse thoroughly and allow drying.
- **Concrete cement:**
- Ensure concrete is fully cured.
- Remove un-cured cement dust, debris and chalky residue with high-pressure washing or scrubbing using a bristle brush and water.
- Use directly on non-porous surface.
- On all absorbent surface such as cement and concrete, reduce the viscosity up to 10%. Apply a thin coat and allow to dry before applying a second coat of non-diluted standard coating.

APPLICATION

- Before use, mix the paint using a 50 to 75mm spiral mixer until a homogeneous solution is obtained
- Use with brush or roller
- When painting porous surfaces thinning (10-15%) is recommended for first coat.
- The ideal application conditions are a surface and ambient temperature of between 10°C to 35°C (and at least 2°C above dew point), with a maximum relative humidity of 50%

MATERIAL SAFETY DATA SHEET

SUPER POLISH PAINT

IDENTIFICATION: Water Base Paint

HEALTH AND SAFETY

- Contact with product may cause irritation to sensitive skin
- Wear suitable gloves for hand protection
- Wear protective clothing
- Wear suitable respirator
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice

FIRST AID

- EYES - Do not rub and flush with plenty of clean water
- SKIN - Wash thoroughly with soap and water immediately after handling

FIRE FIGHTING MEASURES

- Product is not flammable.

ACCIDENTAL SPILLAGE

- Washable with clean water.

PERSONAL PROTECTION

- Use suitable respirator
- Use protective clothing

HANDLING AND STORAGE

- Handling - Wear appropriate personal protective equipment and clothing
- Storage - Store in dry cool conditions and ensure container is sealed
- Store in a well-ventilated area away from foodstuffs, oxidising agents

TRANSPORTATION INFORMATION

- Product must be kept dry during transportation

REGULATORY INFORMATION AND PICTOGRAMS

- Classification: Low hazard
 - Risk Phrases: None
 - Safety Phrases: Wear protective clothing
- In case of contact with eyes, rinse immediately with clean water. If necessary, seek medical advice. After contact with skin, wash with clean water.
- Do not take internally.

CONTACT INFORMATION



admin@superplatina.co.za



016 004 0131



www.superplatina.co.za



Office Address: 74/75 Kroonarend Rd,
Witkopdorp (Daleside), Meyerton, 1873

PRECAUTIONS

- Store away from direct sunlight, heat and severe cold



SUPER PLATINA PAINTS

Super Platina Paints (Pty) Ltd was established 23 years ago and shares a common platform with Hi-Tech Refractories, a leader in the supply of products and materials used in the refractory industry. As a bespoke paint company, we have succeeded in manufacturing a range of paints that are unique in many ways. We've combined the best of European technology with South African practicality at an affordable price.