



- Waterproof
- Easy to apply
- Highly Flexible Membrane
- UV Resistant
- Excellent Chemical Resistance
- Non-Permeable
- Binds to most surfaces
- Weather Resistant
- No fibres - creating a smooth finish
- Dust and dirt wash off

1, 6, 20 litre

COVERS UP TO 5 SQUARE METERS/LITRE!

TOUGH RUBBER SEAL

5-IN-ONE



Galvanized Roofs



Tile Roofs



Fishponds



Gutters



Cement Roofs & Walls



- Roller fits into container
- 20l ToughSealer™ in 24l container to prevent spillage

For optimal results apply a coat of ToughRoof™ over ToughSealer™. The two products is colour matched for improved results.



SUPER PLATINA UPENDE/VERWE/PAINTS

TOUGH TIMES CALL FOR TOUGH SOLUTIONS

CONTACT INFORMATION

- admin@superplatina.co.za
- 016 365 5205
- www.superplatina.co.za
- Office Address: 74/75 Kroonarend Rd, Witkopdorp (Daleside), Meyerton, 1873

We Care:

Made in RSA	Fish Friendly	Water based	Community care
Enviromentally Friendly	SAPMA member	Werkzaam	ichthys



Super Platina Paints (Pty) Ltd was established in 2001 and are working closely with Hi-Tech Refractories. As a bespoke paint company, we have succeeded in manufacturing a range of paints that are unique in many ways. We pride ourselves in combining worldclass technology with South African practicality giving you the best value for money. COMPANY REG. NO: 2001,021579/07

SINCE 2001

TOUGH SEALER™ 5-IN-ONE

APPLICATION INSTRUCTIONS

SURFACE PREPARATION

- It is extremely important to get the surface clean and dry
- Remove dirt, leaves and other debris
- Inspect the entire surface for any open seams, tears, cuts, etc. and fix it with ToughSealer™ and a flexible, reinforcing membrane
- Pressure wash roof with water and allow to dry completely.

BIOLOGICAL CONTROL

- Areas of algae, mildew or fungus should be treated with a solution of 1 part household bleach and 3 parts water, followed by a power washer rinse using clear water.

PRIMING

- ToughSealer™ will adhere to most surfaces without a primer;
- It can be directly applied to cement, galvanize and concrete.
- If ToughSealer™ is used on old paint use a primer to prepare the surface.

APPLICATION INSTRUCTIONS

- Preferably two coats are required.
- It is recommended to paint ToughRoof™ Paint over ToughSealer™ for longer lasting results
- On all absorbent surfaces, thin down first coat with up to 20% water
- Chalky surfaces must be primed with bonding liquid
- ToughSealer™ must be stirred properly
- Allow the first coat to dry for at least 3 hours.
- Apply second coat as soon as the first coat can be safely walked on.
- Coverage rate may decrease on textured surfaces, and more coating will likely be used on first coat than on additional coats.
- Do not apply in temperatures below 10°C, above 35°C, if rain is expected within 2 hours or Humidity above 85%.
- Do not walk on ToughSealer™ other than for periodic maintenance
- Ensure your paint is applied smoothly as ToughSealer™ is designed to give a smooth finish so that dirt can wash off

CLEAN UP & MAINTENANCE

- Application tools and equipment can be cleaned with 100% pure mineral spirits.
- Once a container of ToughSealer™ is opened, the curing process has started. Use the entire product on your project if possible.
- Roof structures may settle over time. A periodic inspection of your roof, which includes transition areas, flashing, vents and skylights, is recommended. Keep drains cleared at all times.
- Roofs become slippery when wet. Use extreme caution.

CAUTION

- An old, neglected, or failing roof does not have the resilience to withstand the rigors of weather. ToughSealer™ may not be suitable for such a roof. If you are in doubt about the condition of your roof, consult a qualified roof inspector.
- Store away from direct sunlight, heat and severe cold
- Use containers with the same batch numbers for large areas

GUARANTEE

- Terms and conditions apply for the Guarantee. See website for more info.

TECHNICAL INFO

- Type: Pure Acrylic Emulsion
- Drying time:
 - Surface Dry: 1-3 hours (depending on temperature)
 - Totally cured: 75-120 hours (depending on temperature)
- Tensile strength: 2 MPa
- Application temperature: 5-35°C
- Flexibility: 100%
- Spreading rate: 3-5m²/litre (depending on surface)
- Gloss Level: Sheen Finish

Colours



**TOUGH TIMES CALL
FOR TOUGH SOLUTIONS**

SUPER PLATINA
OPENDE/VERWE/PAINTS

OUR STORY

During the COVID pandemic when times were tough and the community were hurting two brothers came together to see how they could help. Combining their extremely different skills, experience and personalities, they identified paint products that were needed by the community.

They worked night and day to optimize the product that they have been producing for the last 20 years while keeping the prices low. They looked at innovative packaging that can be reused in order to reduce waste. All of this, while the paint is being made with limited automation in order to create jobs in the community.

Become part of this journey by sending your comments and suggestions for improvements to the brothers at broers@superplatina.co.za. Each comment and suggestion will be read and responded to.

We do not want to waste your money on the marketing of our products. We also know our products lasts so long that you won't have to buy it again soon. Therefore please tell your friends and family so that we can keep our prices low. Enjoy the container

ONS STORIE

Gedurende die COVID 19-pandemie het twee broers gesien hoe swaar die gemeenskap kry. Hulle het besluit om hulle verskillende persoonlikhede en uiteenlopende vaardighede en ervaring te gebruik om te kyk hoe hulle kan help.

Hulle het besluit om op hulle verf produkte te fokus en het begin om dag en nag te werk, om die verwe wat al 20 jaar suksesvol gebruik word, te optimaliseer terwyl hulle die pryse so laag as moontlik hou. Daar is na alle aspekte gekyk insluitende innoverende nuwe verpakking wat hergebruik kan word. Outomatisasie is laag gehou met die vervaardiging, sodat werk geskep kan word in die gemeenskap.

Word gerus deel van hierdie reis deur jou voorstelle vir verbeterings na die broers te stuur na Broers@superplatina.co.za. Elke e-pos sal beantwoord word.

Ons wil nie graag jou geld mors op bemerking van ons produkte nie. Ons weet ook ons produk hou so lank jy gaan dit heel moontlik nooit weer dit hoef te koop nie. So vertel asseblief vir jou vriende en familie van ons verf sodat ons ons prys kan laag hou. Geniet hierdie houer!